



# G•COM

**GX660** MARINE VHF HANDHELD RADIO



The GX660 is a feature packed 5/1 watt IPX7 rated handheld VHF radio that floats.

The unit has a large backlit LCD and large clearly labelled buttons that maximise simplicity of operation.

The GX660 is ideal for dinghies or tenders that need to keep in touch with the 'mother ship' or small boats that don't have electrical systems or sufficient space for a fixed mount radio.



Warranty



Floats



Water Resistant

- > Floats - self buoyant
- > Water resistant to IPX7\*
- > Complete International / USA and Canadian channel sets.
- > Large backlit LCD display and keys
- > Dual watch and priority scan
- > 5/1 watt switchable power
- > Hi capacity 1400mAh Li-Ion rechargeable battery
- > 12 volt battery charger and belt clip included

# GX660 SPECIFICATIONS

## General

<b>Complies with specification</b>	AS/NZS4415.2:2003
<b>Frequency range</b>	155.425 - 162.425
<b>Channel set</b>	Int, USA, CAN, GBR, SCA, HUN
<b>Channel spacing</b>	25 kHz
<b>Modulation</b>	FM
<b>Supply voltage range</b>	7.4 V DC, 1400 mAh Li-Ion rechargeable battery
<b>Frequency stability</b>	+/- 1.5 kHz over temperature range
<b>Dual watch</b>	Yes
<b>Scan speed</b>	10 Ch/sec
<b>LCD dimensions</b>	36 mm (w) x 24 mm (H)
<b>Operation time**</b>	Approximately 12 hrs on a full charge

## Transmitter

<b>Power output</b>	High 5 W max, Low 1W max
<b>Frequency deviation</b>	+/- 5 kHz max
<b>Modulation frequency response</b>	+6 dB per octave, 300 Hz-3 kHz, +1-3 dB
<b>Demodulation S/N</b>	> 40 dB weighted
<b>Current consumption</b>	High - 1.2 amp, Low-550 mA

## Receiver

<b>IF frequencies</b>	1st: 21.4 MHz, 2nd: 450 kHz
<b>Sensitivity</b>	1 uV at 20 dB SINAD
<b>Spurious rejection</b>	> 65 dB
<b>Intermodulation rejection</b>	> 65 dB
<b>Blocking rejection</b>	> 80 dB
<b>Modulation frequency response</b>	-6 dB per octave, 300 Hz-3 kHz,+1-3 dB
<b>Audio output power</b>	600 mW @ 24 Ohms
<b>Current consumption</b>	Full vol: 150 mA, Muted: 50 mA

## Environmental

<b>Temperature range</b>	-15 deg C to + 55 deg C
<b>Compass safe distance</b>	200 mm
<b>Water resistance</b>	IPX7 *

Specifications are typical and are subject to change without notice or obligation.

\* Refer to website for details [www.gme.net.au](http://www.gme.net.au)

\*\* Length of service depends on time spent transmitting and transmit power used.



## GX660 pack includes



## Optional Accessories



BC660  
240 Volt charger

1300 463 463 [gme.net.au](http://gme.net.au)



A division of Standard Communications Pty Ltd.

Head Office: PO Box 96, Winston Hills, NSW 2153, Australia.

New Zealand: PO Box 58, 446 Botany, Auckland 2163 T: (09) 274 0955

All other international enquiries email: [export@gme.net.au](mailto:export@gme.net.au)

Retailer: